

HUAHAI LED







Specs


	Hard module										Soft Module			
Item	indoor						outdoor				indoor			
Pixel Pitch (mm)	1.5625	1.953	2.5	2.6	2.9	3.9	2.6	2.9	3.91	4.81	1.953	2.6	2.9	3.9
LED Confguration	SMD1515	SMD1415	SMD1515	SMD1515	SMD1515 SMD2020	SMD1515	SMD1415	SMD1415	SMD1921	SMD1921	SMD1415	SMD1515	SMD1515 SMD2020	SMD1515
Pixel Density (pixels/㎡)	409,600	262,144	160,000	147,456	112,896	65,536	147,456	112,896	65,536	43,264	262,144	147,456	112,896	65,536
Brightness (cd/㎡)	800–1000	800–1000	800–1000	800–1000	800–1000	800–1000	4,000–4,500	4,000–4,500	4,000–4,500	4,000–4,500	800–1000	800–1000	800–1000	800–1000
Module Size (W x H mm)	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250	250x250
Module Resolution (pixels)	160x160	128x128	100x100	96x96	84x84	64x64	96x96	84x84	64x64	52x52	128x128	96x96	84x84	64x64
Panel Size (W x H mm)	500x500	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000	500x1000
Panel Resolution (pixels)	320x320	256x512	200x400	192x384	172x344	128x256	192x384	172x344	128x256	104x208	256x512	192x384	172x344	128x256
Panel Weight (kg/pc)	7.2kg	10.5kg	10.5kg	10.5kg	10.5kg	10.5kg	10.5kg	10.5kg	10.5kg	10.5kg	4kg	4kg	4kg	4kg
Cabinet Material	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium	Diecast Magnesium
Curveable Angle	Hard Connector: -6°, -3°, 0°, 3°, 6° Soft Connector: -10°, -7.5°, -5°, -2.5°, 0°, 2.5°, 5°, 7.5°, 10°, 12.5°, 15°													
Power Consumption (w/㎡)	450/150	450/150	450/150	450/150	450/150	450/150	700/233	700/233	700/233	700/233	450/150	450/150	450/150	450/150
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz
Gray Scale	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits	14 bits
Ingress Progress	IP30	IP30	IP30	IP30	IP30	IP30	IP65	IP65	IP65	IP65	IP30	IP30	IP30	IP30
Scan Ratio	1/32	1/32	1/25	1/24	1/21	1/16	1/24	1/21	1/16	1/13	1/32	1/24	1/21	1/16

Dimensions






Hard module




Soft Module

IP65 Waterproof (for Outdoor Panel)



Lightweight:10.5kg/pc (21kg/㎡)



Modular, Front or Rear Maintenance

Modular design, fast front or rear maintenance.



rentPad

Indoor & Outdoor Rental Panel

HUAHAI LED


7231 NW 54th street, Miami, Fl 33166

(305) 436-8650

www.huahai.us

Excellent Cooling

The power & data box is comprised of a magnesium enclosure with large cooling fins & the whole chassis, which rapidly dissipates heat, reducing power consumption and improving component operations. rentPad panels will not discolour on full white even under extreme conditions



whole chassis for cooling

Fast Installation


The panel accommodates fast construction with its big & lightweight panels, smart latch & itself assisted system, the installation and disassembly are more efficient than regular panels.




ver latch
push & tighten

hor latch
push, 1/4 turn & tighten

Details of Soft Module Cabinet



Adjustable Curve



1. Slide the latch left and right to adjust the angle




2. Lock the latch



Creative Applications




s-type curve



curve



right angle



column (min. 8 cabinets)

Three Cabinets Available



Hard Connector | Soft Connector | Soft Module